

REPLACED BY
ART 34 AMDT

CLAIMS

1. Video apparatus comprising :

- a digital decoder (6 ; 38) generating a first digital stream (YCbCr₁ ; YCbCr₂) ;
- a video source (2 ; 24) of a first analogue signal;
- a video encoder (12 ; 42) ;
- a first video decoder (4 ; 28) connectable to the video source (2 ; 24) for generating a second digital stream (YCbCr₂ ; YCbCr₁) based on the first analogue signal (CVBS_{in} ; A₁) ;
- mixing means (10, Sync ; 40, Sync) coupled to the first video decoder (4 ; 28) and to the digital decoder (6 ; 38) able to mix the second digital stream (YCbCr₂ ; YCbCr₁) and the first digital stream (YCbCr₁ ; YCbCr₂) into an output digital stream (YCbCr_{out}) to the video encoder (12 ; 42).

2. Video apparatus according to claim 1, wherein a digital encoder (30, 32) generates a third digital stream based on a second analogue signal (A₂) and wherein the digital encoder (30, 32) is connectable to the digital decoder (38) for transmitting said third digital stream to the digital decoder (38).

3. Video apparatus according to claim 2, wherein the digital encoder (30, 32) includes a video decoder (30) for digitising the second analogue signal (A₂).

4. Video apparatus according to claim 2 or 3, wherein the digital encoder (30, 32) and the digital decoder (38) are linked via a digital selector (34).

5. Video apparatus according to claim 4, wherein the digital selector (34) is connected to a medium interface (36).

6. Video apparatus comprising :

- a first video decoder (28) generating a first digital stream (YCbCr₁) based on a first analogue video signal (A₁) ;
- a second video decoder (30) generating a second digital stream (YCbCr₂) based on a second analogue video signal (A₂) ;

- a digital processing unit (32, 34, 36, 38) at least connectable to the second video decoder (30) and able to generate a third digital stream (YCbCr₃) based on the second digital stream (YCbCr₂) ;

5 - a digital switch (40) connected to the first video decoder (28) and to the digital processing unit (32, 34, 36, 38) for selectively outputting to a video encoder (42) the first digital stream (YCbCr₁) or the third digital stream (YCbCr₃) as an output digital stream (YCbCr_{out}).

10 7. Video apparatus according to claim 6, wherein a video encoder (42) outputs an output analogue signal (A_{out} ; R_{out}; G_{out}, B_{out}) based on said output digital stream (YCbCr_{out}).

15 8. Video apparatus according to claim 6 or 7, wherein the digital processing unit includes a medium interface (36).

9. Video apparatus according to claim 8, wherein the medium interface (36) is connectable to the second video decoder (30) for recording on said medium data based on said second digital stream (YCbCr₂).

20 10. Video apparatus according to claim 8 or 9, wherein the medium interface (36) is connectable to the digital switch (40) for outputting to said digital switch (40) a digital stream based on data retrieved from said medium.